

DATASHEET

ANDIVI NDV HIGH

FOR MODELS: ANSI

Model Andivi NDV-High features a more natural and softer form. It is suitable for modern architecture and ambience. This door lock is made of highest quality metal and plastic materials.

SHELL MATERIAL

Stainless steel, easy maintenance matt finish

COLOR

Silver or gold

INTEGRATED CARD READER

NDV HIGH has a built-in RFID reader for contactless Mifare 13.56 MHz cards

MORTISE:

Available as a version with ANSI mortise.
ANSI mortise is adaptable to door thickness: 36 ~ 60 mm,
door frame width: ≥ 120 mm.

SAFETY

- Anti-panic function
- Anti-burglar bolt

SHOCK DURABILITY:

More than 1000 kg

WORKING ENVIRONMENT:

- temperature: $-20 \sim +50$ °C
- humidity: $\leq 95\%$,
- without corrosive gas and dust

POWER SUPPLY:

The power supply of the **NDV-HIGH** door lock is DC6V.
Every door lock needs **4 × AA alkaline batteries**.
Batteries are accessible from the inner side of the door lock and are easy replaceable. The batteries are not included in the door lock set.

LOW POWER ALARM at $4.8V \pm 3\%$ (once battery is low the door lock starts beeping, while 30 entrances are still possible)



WEIGHT

~ 3,1 kg

DIMENSIONS

269 × 77 (158 with handle) mm

DRILLING INSTRUCTIONS DOWNLOAD

In PDF and DWG:

- Download [ANSI](#)

INCLUDED WITH 1 × NDV HIGH DOOR LOCK

- Front side of the door lock with handle,
- Backside side of the door lock with handle
- Mortise,
- side plate,
- 2 standard keys (for mechanical entry)
- strike plate,
- plastic housing,
- screws,
- shaft

CERTIFICATION

- CE RED (Radio Equipment Directive) certificate
- EN 12209 for fire safety