

DATASHEET

ANDIVI NDV SLIM

FOR MODELS: ANSI & EURO

Model Andivi NDV-Slim has slim and elegant frame that is thinner and larger than other models. A hook with an elegant frame without subtle curves made of highest quality metal and plastic materials combines minimalism with a touch of modern elegance.

SHELL MATERIAL

Stainless steel, easy maintenance matt finish

COLOR

Silver or gold

INTEGRATED CARD READER

NDV TALL has a built-in RFID reader for contactless Mifare 13.56 MHz cards

MORTISE:

Available as a version with ANSI mortise or EURO mortise.

ANSI mortise is adaptable to door thickness: 36 ~ 60 mm, door frame width: ≥ 120 mm.

EURO mortise is adaptable to door thickness: 30 ~ 60 mm, door frame width: ≥ 90 mm

SAFETY

- Anti-panic function
- Anti-burglar bolt

SHOCK DURABILITY:

More than 1000 kg

WORKING ENVIRONMENT:

- temperature: $-20 \sim +50$ °C
- humidity: $\leq 95\%$,
- without corrosive gas and dust

POWER SUPPLY:

The power supply of the **NDV-SLIM** door lock is DC6V. Every door lock needs **4 × AA alkaline batteries**. Batteries are accessible from the inner side of the door lock and are easy replaceable. The batteries are not included in the door lock set.

LOW POWER ALARM at $4.8V \pm 3\%$ (once battery is low the door lock starts beeping, while 30 entrances are still possible)



WEIGHT

~ 2,8 kg

DIMENSIONS

280 × 50 (135 with handle) mm

DRILLING INSTRUCTIONS DOWNLOAD

In PDF and DWG:

- Download [ANSI](#)
- Download [EURO](#)

INCLUDED WITH 1 × NDV SLIM DOOR LOCK

- Front side of the door lock with handle,
- Backside side of the door lock with handle
- Mortise,
- side plate,
- 2 standard keys (for mechanical entry)
- strike plate,
- plastic housing,
- screws,
- shaft

CERTIFICATION

- CE RED (Radio Equipment Directive) certificate
- EN 12209 for fire safety